

Product Datasheet

Tracerco™ PED2-IS

Personal Electronic Dosimeter

Built on over a decade of user experience, the Tracerco™ Personal Electronic Dosimeter 2 (PED2) is a rugged, compact, grab-and-go device that is easy to use, easy to manage and offers leading edge radiation protection.

The flexible device measures, records and displays dose rate and accumulated dose in real time with up to four configurable dose and dose rate alarm settings that trigger audible, visual, textual and haptic alerts.

A single button is used to navigate an intuitive carousel menu and a large, easy-to-read colour display ensures that vital information is clear and simple to understand providing unparalleled situational awareness.

Exposure data is automatically logged into a self-managing memory and can be seamlessly and securely transferred into the Tracerco™ DoseVision™ software platform for simple reporting and visualisation. DoseVision™ enables straightforward device configuration and offers optional cloud-based services ensuring secure, auditable, and efficient management of equipment and worker dose data.



Features

- Clear and readable transfective display enables use in dimly lit or sun-glare scenarios.
- Responds promptly to small changes in radiation whilst also being capable of making accurate and reliable readings in hot zone fields up to 1 Sv/h.
- Powered by commercially available rechargeable or replaceable batteries.
- Secure NFC data download via charging dock also with USB C connection.
- PED2+ and PED2-IS+ are BLE and GPS enabled, have enhanced alarm messaging, and can operate in off-body mode for handheld surveys and perimeter monitoring tasks.
- Intrinsically safe variants (PED2-IS and PED2-IS+) cater for use in hazardous areas.
- DoseVision™ companion software with optional cloud ecosystem.

Applications

- Emergency responders and security services.
- Offshore and onshore oil and gas.
- Industrial radiography.
- Border control and military (CBRNe)
- Nuclear and decommissioning.
- Medical and life sciences.
- Mining.

Specifications

Performance	
Radiation Detected	Gamma and X-rays detected Photon energy response: 33keV to 3MeV (non-I.S. variants) 48keV to 3MeV (I.S. variants)
Detector	Geiger Müller tube (with RapidResponse technology for increased range and high sensitivity)
Device Memory	250 MB self-managing device storage capacity. (i.e. > 1 million records) – Personal dose operation > 10 years of dose records (including GPS data) – Survey mode > 1 year continuous area monitoring logging every 2 seconds
Accumulated Dose Range**	0 μ Sv - 42 Sv (0 mrem - 4200 rem) Dose increments of 0.01 μ Sv (0.001 mrem)
Dose Rate Range**	Standard calibration: 0 μ Sv - 100 mSv/h (0 mrem/h-10 rem/h) Extended range calibration: 0 μ Sv - 1 Sv/h (0 mrem/h -100 rem/h) N.B. Detection limit 0.12 μ Sv/h. Devices display up to 200% of the calibrated range
Screen Type	2" TFT Transflective, 65k full colour 240*320 pixels (screen rotate feature)
Configurable Alarms	Audible, visual, haptic. Up to 4 dose alarms and 4 dose rate alarms
Non-volatile Memory	NVM data retention > 10 years
Mechanical Characteristics	
Size	102 mm x 63 mm x 31 mm
Weight	> 200 g
Case Material	– Shock, vibration and drop resistant polymers with antistatic properties – Front replaceable protective membrane (anti-tamper)

Electrical Characteristics	
Battery Options***	2 x AAA 1.2V NiMH rechargeable cells or 2 x AAA 1.5V Alkaline disposable cells
Real Time Clock	Secondary cell RTC battery back-up and primary cell removal detection
Physical Sensors	– Accelerometer – Temperature
Charging/Data Download	– PED2, PED2+ via supplied USB C cable (Charging dock is an option for above devices) – PED2-IS, PED2-IS+ via supplied charging dock in non-hazardous area only (N.B. All devices can operate whilst on charge)
Comms/Location	– PED2-IS: NFC – PED2+: NFC, BLE 5, GPS – PED2-IS+: NFC, BLE 5, GPS
Environmental	
Ingress Protection Rating	IP67 (dust tight and immersion in water at depth of 1 m)
Hazardous Area Classification Code	PED2-IS, PED2-IS+ only) ATEX and IECEx: Zone 0, 1, 2 gas group IIA, IIB, IIC
Standard Compliance	BS EN 61526 – 2013; IEC 61526:2010; ANSI42.20:2003; EN55011; IEC60079-0; IEC60079-11; IEC61010-1
Humidity	Up to 95%
Temperature	-20°C to 50°C
Hazardous Area Certification Code	(PED2-IS, PED2-IS+ only) ATEX Marking – II 1G Ex ia IIC T4 Ga (-20°C ≤ Ta ≤ +50°C) IECEx Marking – Ex ia IIC T4 Ga (-20°C ≤ Ta ≤ +50°C) UKEx Marking – Ex ia IIC T4 Ga (-20°C ≤ Ta ≤ +50°C)

Specifications are subject to change without notice.

For the most up-to-date specifications, please visit www.tracerco.com

*For detailed response curve please see report by Radiation Metrology, UKHSA.

** Accumulated dose indicated relates to personal dose equivalent Hp(10). Corresponding dose rate indicated relates to personal dose equivalent rate except where plus variants are used in Survey mode where the rate indication is related to the ambient dose equivalent H*(10).

*** Specified batteries must be used for IS variants. See user manual for permitted battery types.

Southern Scientific Limited

Scientific House, The Henfield Business Park
Shoreham Road, Henfield, BN5 9SL, UK

E-mail: info@southernscientific.co.uk

Tel: +44 (0)1273 497600

www.southernscientific.co.uk